



2N® Helios IP Safety

2N® Helios IP Safety is a first-class security intercom designed for emergency communications. No matter whether it is inundated or exposed to -40°C frost; it remains fully functional and allows you to reach help at once. In addition, thanks to its orange colour it is easy to locate in poor visibility.



Logistics and transport
Industrial zones
Public spaces

Schools and campuses
State administration public
buildings

Communications under all conditions

Get high-quality sound even in challenging circumstances thanks to HD audio with automatic volume adjustment and IP69K and IK10 grade extreme endurance.

Always visible and functional

You can rely on the distinctive orange colouring and blue backlit buttons. You will never find this intercom hard to find when you need it.

Integration into your existing system

Increase the reach of emergency announcements. Thanks to its 10 W amplifier you can use 2N® Helios IP Safety as a loudspeaker for public address.

2N® Helios IP Safety

FEATURES & BENEFITS

SIP support with no server needed

Thanks to SIP protocol support the intercom can link easily with IP phones and PBX from other producers, without having to connect to the server.

Security relay

This simple additional device prevents manipulation with the lock, preventing unauthorized intrusion.

Tamper switch

The 2N IP intercom can be fitted with a tamper switch that detects unauthorized device intrusions.

Time profiles

Thanks to this function you can define in what period of time the phone number is valid.


Backlit buttons

2N® Helios IP Safety features 1 or 2 keys which are distinctively backlit in blue.

Audio loop test

The intercom regularly performs audio self tests. In the event of a failure of the microphone or speaker, it reports the problem.

DIAGRAM



TECHNICAL PARAMETERS

Signalling protocol

SIP 2.0 (RFC - 3261)

Button

Button design metal buttons with blue backlight or a red emergency button

Number of buttons 1 or 2

Numeric keypad No

Audio

Microphone 2 built-in microphones

Speaker 10W

Sound pressure at 1 kHz at 1 m distance 94dB (10W speaker)

Audio stream

Codecs G.711, G.729, G.722, L16/16kHz

Interfaces

Power supply 12V±15%/2A DC or PoE

PoE PoE 802.3af (Class 0 - 12.95W)

LAN 10/100BASE-TX with Auto-MDIX

Passive switch NC/NO contacts, max 30 V/1 A AC/DC

Active switch output 9 to 13 V DC depending on Power supply (PoE: 9 V; adapter: source voltage minus 1 V), max 700 mA

Mechanical properties

Weight max. 2000 g

Operating temperature -40°C - 55°C

Storage temperature -40°C - 70°C

Operating relative humidity 10%-95% (non-condensing)

Dimensions 217x109x83 mm

Ingress Protection IP69K

SOFTWARE

2N® Access Commander - software to manage 2N IP intercoms and access units

2N® Network Scanner - application for detecting 2N IP intercoms and access control units on the network

2N® Helios IP Mobile - application for opening the door remotely with a mobile phone